

# **FW-PIA N&A Pineapple Flavor**

Flavor West Manufacturing, LLC.

Version No: **1.1**Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Chemwatch Hazard Alert Code: 2

Issue Date: 05/24/2021 Print Date: 05/24/2021 Initial Date: 05/24/2021

L.GHS.USA.EN

#### SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

# **Product Identifier**

Product name	FW-PIA N&A Pineapple Flavor			
Synonyms	Available			
Proper shipping name	xtracts, flavoring, liquid			
Other means of identification	Not Available			

# Relevant identified uses of the substance or mixture and uses advised against

Relevant identified	Use according to manufacturer's directions.
uses	obs decorating to manufacturer of discontinuous

# Details of the manufacturer/importer

Registered company name	Flavor West Manufacturing, LLC.
Address	29400 Hunco Way, Lake Elsinore CA 92530 United States
Telephone	(951) 893-5120
Fax	(714) 276-1621
Website	www.FlavorWest.com
Email	Flavor@FlavorWest.com

# **Emergency telephone number**

Association / Organisation	Chemwatch
Emergency telephone numbers	see below
Other emergency telephone numbers	see below

## **CHEMWATCH EMERGENCY RESPONSE**

Primary Number	Alternative Number 1	Alternative Number 2	
877 715 9305	+612 9186 1132	Not Available	

Once connected and if the message is not in your prefered language then please dial 01

Una vez conectado y si el mensaje no está en su idioma preferido, por favor marque 02

## **SECTION 2 HAZARDS IDENTIFICATION**

#### Classification of the substance or mixture

# FW-PIA N&A Pineapple Flavor



**GHS Classification** 

Eye Irritation Category 2A, Flammable Liquid Category 3

## Label elements

# GHS label elements





SIGNAL WORD

WARNING

## Hazard statement(s)

H319	Causes serious eye irritation
H226	Flammable liquid and vapour

# Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.		
P233	Keep container tightly closed.		
P240	Ground/bond container and receiving equipment.		
P241	Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment.		
P242	Use only non-sparking tools.		
P243	Take precautionary measures against static discharge.		
P280	Wear protective gloves/protective clothing/eye protection/face protection.		

# Precautionary statement(s) Response

P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam for extinction.		
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
P337+P313	If eye irritation persists: Get medical advice/attention.		
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.		

# Precautionary statement(s) Storage

P403+P235 Store in a well-ventilated place. Keep cool.

# Precautionary statement(s) Disposal

Dispose of contents/container to authorised chemical landfill or if organic to high temperature incineration

# **SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**

## **Substances**

See section below for composition of Mixtures

## **Mixtures**

CAS No	%[weight]	Name
57-55-6	60-70	propylene glycol
141-78-6	1-5	ethyl acetate
123-66-0	1-5	ethyl butyl acetate
102-76-1	30-40	glyceryl triacetate

 Version No: 1.1
 Page 3 of 12
 Issue Date: 05/24/202\*

 Print Date: 05/24/202\*
 Print Date: 05/24/202\*

#### FW-PIA N&A Pineapple Flavor

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

#### **SECTION 4 FIRST AID MEASURES**

### Description of first aid measures

Eye Contact	If this product comes in contact with the eyes:  Wash out immediately with fresh running water.  Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occas lifting the upper and lower lids.  Seek medical attention without delay; if pain persists or recurs seek medical attention.  Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.			
Skin Contact	If skin contact occurs:  ► Immediately remove all contaminated clothing, including footwear.  ► Flush skin and hair with running water (and soap if available).  ► Seek medical attention in event of irritation.			
Inhalation	<ul> <li>If fumes or combustion products are inhaled remove from contaminated area.</li> <li>Lay patient down. Keep warm and rested.</li> <li>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>Transport to hospital, or doctor.</li> </ul>			
Ingestion	<ul> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Seek medical advice.</li> </ul>			

# Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

- Polyethylene glycols are generally poorly absorbed orally and are mostly unchanged by the kidney.
- Dermal absorption can occur across damaged skin (e.g. through burns) leading to increased osmolality, anion gap metabolic acidosis, elevated calcium, low ionised calcium, CNS depression and renal failure.
- Treatment consists of supportive care.

[Ellenhorn and Barceloux: Medical Toxicology]

Propylene glycol is primarily a CNS depressant in large doses and may cause hypoglycaemia, lactic acidosis and seizures.

- The usual measures are supportive care and decontamination (Ipecac/ lavage/ activated charcoal/ cathartics), within 2 hours of exposure should suffice.
- Check the anion gap, arterial pH, renal function and glucose levels.

Ellenhorn and Barceloux: Medical Toxicology

# **SECTION 5 FIREFIGHTING MEASURES**

## Extinguishing media

- ▶ Alcohol stable foam.
- Dry chemical powder.
- ▶ BCF (where regulations permit).
- Carbon dioxide.

# Special hazards arising from the substrate or mixture

Fire Incompatibility

 Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

# Advice for firefighters

## Fire Fighting

- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- ▶ May be violently or explosively reactive.
- ▶ Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.

 Version No: 1.1
 Page 4 of 12
 Issue Date: 05/24/2021 Print Date: 05/24/2021

#### FW-PIA N&A Pineapple Flavor

## Fire/Explosion Hazard

- ▶ Liquid and vapour are flammable.
- ▶ Moderate fire hazard when exposed to heat or flame.
- Vapour forms an explosive mixture with air.
- Moderate explosion hazard when exposed to heat or flame.

#### **SECTION 6 ACCIDENTAL RELEASE MEASURES**

# Personal precautions, protective equipment and emergency procedures

#### Minor Spills

- ▶ Remove all ignition sources.
- ▶ Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- ▶ Control personal contact with the substance, by using protective equipment.

Chemical Class: alcohols and glycols

For release onto land: recommended sorbents listed in order of priority.

SORBENT TYPE	RANK	APPLICATION	COLLECTION	LIMITATIONS
-----------------	------	-------------	------------	-------------

#### LAND SPILL - SMALL

cross-linked polymer - particulate		shovel	shovel	R, W, SS
cross-linked polymer - pillow		throw	pitchfork	R, DGC, RT
sorbent clay - particulate		shovel	shovel	R,I, P
wood fiber - pillow	3	throw	pitchfork	R, P, DGC, RT
treated wood fiber - pillow	3	throw	pitchfork	DGC, RT
foamed glass - pillow	4	throw	pichfork	R, P, DGC, RT

#### LAND SPILL - MEDIUM

## Major Spills

cross-linked polymer - particulate	1	blower	skiploader	R,W, SS
polypropylene - particulate	2	blower	skiploader	W, SS, DGC
sorbent clay - particulate	2	blower	skiploader	R, I, W, P, DGC
polypropylene - mat	3	throw	skiploader	DGC, RT
expanded mineral - particulate	3	blower	skiploader	R, I, W, P, DGC
polyurethane - mat	4	throw	skiploader	DGC, RT

# Legend

DGC: Not effective where ground cover is dense

R; Not reusable

I: Not incinerable

P: Effectiveness reduced when rainy

RT:Not effective where terrain is rugged

SS: Not for use within environmentally sensitive sites

W: Effectiveness reduced when windy

Reference: Sorbents for Liquid Hazardous Substance Cleanup and Control;

R.W Melvold et al: Pollution Technology Review No. 150: Noyes Data Corporation 1988

- ▶ Clear area of personnel and move upwind.
- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- ▶ May be violently or explosively reactive.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

#### **SECTION 7 HANDLING AND STORAGE**

# Precautions for safe handling

- ► Containers, even those that have been emptied, may contain explosive vapours.
- ▶ Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- ▶ DO NOT allow clothing wet with material to stay in contact with skin

#### Safe handling

Rags wet / soaked with unsaturated hydrocarbons / drying oils may auto-oxidise; generate heat and, in-time, smoulder and ignite. This is especially the case where oil-soaked materials are folded, bunched, compressed, or piled together - this allows the heat to accumulate or even accelerate the reaction

Oily cleaning rags should be collected regularly and immersed in water, or spread to dry in safe-place away from direct sunlight or stored, immersed, in solvents in suitably closed containers.

 Version No: 1.1
 Issue Date: 05/24/202\*

 Page 5 of 12
 Print Date: 05/24/202\*

# FW-PIA N&A Pineapple Flavor

### Other information

- Store in original containers in approved flammable liquid storage area.
- Store away from incompatible materials in a cool, dry, well-ventilated area.
- ▶ DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- ▶ No smoking, naked lights, heat or ignition sources.

# Conditions for safe storage, including any incompatibilities

#### Suitable container

- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.
- ▶ For low viscosity materials (i): Drums and jerry cans must be of the non-removable head type.

# Storage

incompatibility

• Glycols and their ethers undergo violent decomposition in contact with 70% perchloric acid. This seems likely to involve formation of the glycol perchlorate esters (after scission of ethers) which are explosive, those of ethylene glycol and 3-chloro-1,2-propanediol being more powerful than glyceryl nitrate, and the former so sensitive that it explodes on addition of water.

#### Alcohols

- are incompatible with strong acids, acid chlorides, acid anhydrides, oxidising and reducing agents.
- reacts, possibly violently, with alkaline metals and alkaline earth metals to produce hydrogen
- react with strong acids, strong caustics, aliphatic amines, isocyanates, acetaldehyde, benzoyl peroxide, chromic acid, chromium oxide, dialkylzincs, dichlorine oxide, ethylene oxide, hypochlorous acid, isopropyl chlorocarbonate, lithium tetrahydroaluminate, nitrogen dioxide, pentafluoroguanidine, phosphorus halides, phosphorus pentasulfide, tangerine oil, triethylaluminium, triisobutylaluminium
- ▶ should not be heated above 49 deg.

#### PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

#### SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

## **Control parameters**

## OCCUPATIONAL EXPOSURE LIMITS (OEL)

# INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Levels (PELs) - Table Z1	ethyl acetate	Ethyl acetate	1400 mg/m3 / 400 ppm	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	ethyl acetate	Ethyl acetate	400 ppm	Not Available	Not Available	TLV® Basis: URT & eye irr
US NIOSH Recommended Exposure Limits (RELs)	ethyl acetate	Acetic ester, Acetic ether, Ethyl ester of acetic acid, Ethyl ethanoate	1400 mg/m3 / 400 ppm	Not Available	Not Available	Not Available

## **EMERGENCY LIMITS**

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
propylene glycol	Propylene glycol; (1,2-Propanediol)	30 mg/m3	1300 mg/m3	7900 mg/m3
ethyl acetate	Ethyl acetate	400 ppm	400 ppm	10000 ppm
glyceryl triacetate	Triacetin; (Triacetyl glycerin)	9 mg/m3	99 mg/m3	590 mg/m3

Ingredient	Original IDLH	Revised IDLH
propylene glycol	Not Available	Not Available
ethyl acetate	10,000 ppm	2,000 [LEL] ppm
ethyl butyl acetate	Not Available	Not Available
glyceryl triacetate	Not Available	Not Available

#### MATERIAL DATA

For ethyl acetate:

Odour Threshold Value: 6.4-50 ppm (detection), 13.3-75 ppm (recognition)

The TLV-TWA provides a significant margin of safety from the standpoint of adverse health effects. Unacclimated subjects found the odour objectionably strong at 200 ppm. Mild nose, eye and throat irritation was experienced at 400 ppm. Workers exposed regularly at concentrations ranging from 375 ppm to 1500 ppm for several months showed no unusual signs or symptoms.

#### FW-PIA N&A Pineapple Flavor

## **Exposure controls**

# Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

#### Personal protection











# Eye and face protection

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.

#### Skin protection

#### See Hand protection below

- ▶ Wear chemical protective gloves, e.g. PVC.

## Hands/feet protection

- Wear safety footwear or safety gumboots, e.g. Rubber NOTE:
- ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

#### Body protection

# See Other protection below

## Other protection

- Overalls.
- PVC Apron.PVC protective suit may be required if exposure severe.
- Evewash unit.
- Thermal hazards

#### Not Available

# Recommended material(s)

## **GLOVE SELECTION INDEX**

Glove selection is based on a modified presentation of the:

#### "Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

FW-PIA N&A Pineapple Flavor

Material	СРІ
PE/EVAL/PE	A
BUTYL	С
BUTYL/NEOPRENE	С
CPE	С
HYPALON	С
NATURAL RUBBER	С
NATURAL+NEOPRENE	С
NEOPRENE	С
NEOPRENE/NATURAL	С
NITRILE	С
NITRILE+PVC	С
PVA	С
PVC	С
SARANEX-23	С
SARANEX-23 2-PLY	С
TEFLON	С
VITON/CHLOROBUTYL	С

<sup>\*</sup> CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

# Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	Air-line*	A-2 P2	A-PAPR-2 P2 ^
up to 20 x ES	-	A-3 P2	-
20+ x ES	-	Air-line**	-

\* - Continuous-flow; \*\* - Continuous-flow or positive pressure demand ^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

 Version No: 1.1
 Page 7 of 12
 Issue Date: 05/24/2021

 Print Date: 05/24/2021
 Print Date: 05/24/2021

## FW-PIA N&A Pineapple Flavor

C: Poor to Dangerous Choice for other than short term immersion NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. 
\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

#### **SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

# Information on basic physical and chemical properties

Appearance	Clear to light yellow		
Physical state	Liquid	Relative density (Water = 1)	1.05
Odour	Characteristic	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	54.5	Taste	Pineapple
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Flammable.	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

## **SECTION 10 STABILITY AND REACTIVITY**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

## **SECTION 11 TOXICOLOGICAL INFORMATION**

# Information on toxicological effects

Inhaled

The material is not thought to produce respiratory irritation (as classified by EC Directives using animal models). Nevertheless inhalation of vapours, fumes or aerosols, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress.

Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.

 Version No: 1.1
 Page 8 of 12
 Issue Date: 05/24/2021

 Print Date: 05/24/2021
 Print Date: 05/24/2021

## FW-PIA N&A Pineapple Flavor

## Accidental ingestion of the material may be damaging to the health of the individual. Ingestion of propylene glycol produced reversible central nervous system depression in humans following ingestion of 60 ml. Symptoms included increased heart-rate (tachycardia), excessive sweating (diaphoresis) and grand mal seizures in a 15 Ingestion month child who ingested large doses (7.5 ml/day for 8 days) as an ingredient of vitamin preparation. Excessive repeated ingestions may cause hypoglycaemia (low levels of glucose in the blood stream) among susceptible individuals; this may result in muscular weakness, incoordination and mental confusion. Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. The material may produce moderate skin irritation; limited evidence or practical experience suggests, that the material either: ▶ produces moderate inflammation of the skin in a substantial number of individuals following direct contact and/or Skin Contact • produces significant, but moderate, inflammation when applied to the healthy intact skin of animals (for up to four hours), such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Eve Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur. Irritation of the eyes may produce a heavy secretion of tears (lachrymation). Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems. There exists limited evidence that shows that skin contact with the material is capable either of inducing a sensitisation Chronic reaction in a significant number of individuals, and/or of producing positive response in experimental animals Glyceryl triesters (triglycerides), following ingestion, are metabolised to monoglycerides, free fatty acids and glycerol, all of which are absorbed in the intestinal mucosa and undergo further metabolism. Medium chain triglycerides (C8-C10) appear to have relatively rapid metabolism and elimination from blood and tissues compared to long chain triglycerides (C16-C18). TOXICITY IRRITATION FW-PIA N&A Pineapple Flavor Not Available Not Available TOXICITY IRRITATION Dermal (rabbit) LD50: >2000 mg/kg<sup>[1]</sup> Eye (rabbit): 100 mg - mild Oral (rat) LD50: 20000 mg/kgd<sup>[2]</sup> propylene glycol Eye (rabbit): 500 mg/24h - mild Skin(human):104 mg/3d Intermit Mod Skin(human):500 mg/7days mild IRRITATION Dermal (rabbit) LD50: >18000 mg/kg<sup>[2]</sup> Eye (human): 400 ppm Inhalation (mouse) LC50: >18 mg/l4 h<sup>[1]</sup> Inhalation (mouse) LC50: 33.5 mg/l2 h<sup>[1]</sup> Inhalation (mouse) LC50: 45 mg/L/2H<sup>[2]</sup> ethyl acetate Inhalation (rat) LC50: >6000 ppm/6H<sup>[2]</sup> Inhalation (rat) LC50: 1600 ppm/8h<sup>[2]</sup> Inhalation (rat) LC50: 200 mg/l1 h<sup>[1]</sup> Oral (rat) LD50: 10170 mg/kg<sup>[1]</sup> TOXICITY IRRITATION ethyl butyl acetate Dermal (rabbit) LD50: >2000 mg/kg<sup>[1]</sup> Skin (rabbit): 500 mg/24h - mod Oral (rat) LD50: >2000 mg/kg<sup>[1]</sup> TOXICITY IRRITATION Dermal (rabbit) LD50: >5000 mg/kg<sup>[1]</sup> [Manufacturer]\* glyceryl triacetate Oral (rat) LD50: >2000 mg/kg<sup>[1]</sup>

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.\* Value obtained from manufacturer's msds.

 Version No: 1.1
 Page 9 of 12
 Issue Date: 05/24/2021

 Print Date: 05/24/2021
 Print Date: 05/24/2021

#### FW-PIA N&A Pineapple Flavor

Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

# FW-PIA N&A Pineapple Flavor

The acute oral toxicity of propylene glycol is very low, and large quantities are required to cause perceptible health damage in humans. Serious toxicity generally occurs only at plasma concentrations over 1 g/L, which requires extremely high intake over a relatively short period of time. It would be nearly impossible to reach toxic levels by consuming foods or supplements, which contain at most 1 g/kg of PG. Cases of propylene glycol poisoning are usually related to either inappropriate intravenous administration or accidental ingestion of large quantities by children. The potential for long-term oral toxicity is also low.

# PROPYLENE GLYCOL

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

The acute oral toxicity of propylene glycol is very low, and large quantities are required to cause perceptible health damage in humans.

# ETHYL BUTYL ACETATE

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS.

Acute Toxicity	0	Carcinogenicity	0
Skin Irritation/Corrosion	0	Reproductivity	0
Serious Eye Damage/Irritation	<b>~</b>	STOT - Single Exposure	0
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0
Mutagenicity	0	Aspiration Hazard	0

Legend:

✓ – Data required to make classification available

🗶 – Data available but does not fill the criteria for classification

Not Available to make classification

### **CMR STATUS**

Not Applicable

## **SECTION 12 ECOLOGICAL INFORMATION**

# Toxicity

#### NOT AVAILABLE

-						
Ingredient	Endpoint	Test Duration	Effect	Value	Species	BCF
propylene glycol	Not Available					
ethyl acetate	Not Available					
ethyl butyl acetate	Not Available					
glyceryl triacetate	Not Available					

Propylene glycol is known to exert high levels of biochemical oxygen demand (BOD) during degradation in surface waters. This process can adversely affect aquatic life by consuming oxygen needed by aquatic organisms for survival. Large quantities of dissolved oxygen (DO) in the water column are consumed when microbial populations decompose propylene glycol.

Sufficient dissolved oxygen levels in surface waters are critical for the survival of fish, macro-invertebrates, and other aquatic organisms.

## Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
propylene glycol	LOW	LOW
ethyl acetate	LOW (Half-life = 14 days)	LOW (Half-life = 14.71 days)
ethyl butyl acetate	LOW	LOW

 Version No: 1.1
 Page 10 of 12
 Issue Date: 05/24/2021

 Print Date: 05/24/2021

# FW-PIA N&A Pineapple Flavor

glyceryl triacetate	LOW	LOW

# **Bioaccumulative potential**

Ingredient	Bioaccumulation
propylene glycol	LOW (BCF = 1)
ethyl acetate	HIGH (BCF = 3300)
ethyl butyl acetate	LOW (LogKOW = 2.8286)
glyceryl triacetate	LOW (BCF = 1.3)

# Mobility in soil

Ingredient	Mobility
propylene glycol	HIGH (KOC = 1)
ethyl acetate	LOW (KOC = 6.131)
ethyl butyl acetate	LOW (KOC = 74.33)
glyceryl triacetate	LOW (KOC = 48.06)

#### **SECTION 13 DISPOSAL CONSIDERATIONS**

## Waste treatment methods

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

Product / Packaging disposal

- Reduction
- Reuse
- Recycling
- ▶ Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.

# **SECTION 14 TRANSPORT INFORMATION**

# **Labels Required**



**Marine Pollutant** 

NO

# Land transport (DOT)

UN number	1197
Packing group	III
UN proper shipping name	Extracts, flavoring, liquid
Environmental hazard	No relevant data
Transport hazard class(es)	Class 3
Special precautions for user	Special provisions 149, IB2, T4, TP1, TP8

# Air transport (ICAO-IATA / DGR)

UN number	1197
Packing group	III
UN proper shipping name	Extracts, flavouring, liquid
Environmental hazard	No relevant data

 Version No: 1.1
 Page 11 of 12
 Issue Date: 05/24/2021

 Print Date: 05/24/2021
 Print Date: 05/24/2021

# FW-PIA N&A Pineapple Flavor

Transport hazard class(es)  ICAO / IATA Subrisk Not Applicable ERG Code  Special provisions Cargo Only Packing Instructions Gargo Only Maximum Qty / Pack Passenger and Cargo Packing Instructions  Passenger and Cargo Maximum Qty / Pack Passenger and Cargo Limited Quantity Packing Instructions Y344				
Class(es)    CAO / IAIA Subrisk   Not Applicable	T	ICAO/IATA Class	3	
Special precautions for user  Special precautions for user  Special precautions and Cargo Packing Instructions  Cargo Only Maximum Qty / Pack and Cargo Packing Instructions and Cargo Packing Instructions and Cargo Packing Instructions and Cargo Packing Instructions and Cargo Limited Quantity Packing Instructions and	•	ICAO / IATA Subrisk	Not Applicable	
Cargo Only Packing Instructions 366  Cargo Only Maximum Qty / Pack 220 L  Passenger and Cargo Packing Instructions 355  Passenger and Cargo Maximum Qty / Pack 60 L  Passenger and Cargo Limited Quantity Packing Instructions Y344	5.005(00)	ERG Code	3L	
Cargo Only Packing Instructions 366  Cargo Only Maximum Qty / Pack 220 L  Passenger and Cargo Packing Instructions 355  Passenger and Cargo Maximum Qty / Pack 60 L  Passenger and Cargo Limited Quantity Packing Instructions Y344				
Cargo Only Maximum Qty / Pack 220 L  Passenger and Cargo Packing Instructions 355  Passenger and Cargo Maximum Qty / Pack 60 L  Passenger and Cargo Limited Quantity Packing Instructions Y344		Special provisions		А3
Passenger and Cargo Packing Instructions  Passenger and Cargo Maximum Qty / Pack  Passenger and Cargo Limited Quantity Packing Instructions Y344		Cargo Only Packing Instructions		366
Fassenger and Cargo Packing Instructions 355  Passenger and Cargo Maximum Qty / Pack 60 L  Passenger and Cargo Limited Quantity Packing Instructions Y344		Cargo Only Maximum Qty / Pack		220 L
Passenger and Cargo Maximum Qty / Pack 60 L Passenger and Cargo Limited Quantity Packing Instructions Y344	• •	Passenger and Cargo Packing Instructions		355
		Passenger and Cargo Maximum Qty / Pack		60 L
		Passenger and Cargo Limited Quantity Packing Instructions		Y344
Passenger and Cargo Limited Maximum Qty / Pack 10 L		Passenger and Cargo Limited Maximum Qty / Pack		10 L

# Sea transport (IMDG-Code / GGVSee)

UN number	1197	
Packing group	III	
UN proper shipping name	EXTRACTS, FLAVOURING, LIQUID	
Environmental hazard	Not Applicable	
Transport hazard class(es)	IMDG Class 3 IMDG Subrisk Not Applicable	
Special precautions for user	EMS Number F-E , S-D Special provisions 223 955 Limited Quantities 5 L	

# Transport in bulk according to Annex II of MARPOL 73 / 78 and the IBC code

Source	Ingredient	Pollution Category
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	ethyl acetate	Z
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	ethyl butyl acetate	Y
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	glyceryl triacetate	Z

# **SECTION 15 REGULATORY INFORMATION**

# Safety, health and environmental regulations / legislation specific for the substance or mixture

propyle glycol(57-55-6 found on t following regulate li	is SQER and de minimis emission values", "US Alface Environmental Exposure Levels (WEELs)", "US Spacecraft  Maximum Allowable Concentrations (SMACs) for Airborne Contaminants". "US Toxic Substances Control Act (TSCA) -
ethyl acetate(141-78 is found on t following regulate li	California Permissible Exposure Limits for Chemical Contaminants", "US - Idaho - Limits for Air Contaminants", "US - Vermont

 Version No: 1.1
 Page 12 of 12
 Issue Date: 05/24/2021

 Print Date: 05/24/2021
 Print Date: 05/24/2021

# FW-PIA N&A Pineapple Flavor

	Recommended Exposure Limits (RELs)", "US - Washington Permissible exposure limits of air contaminants", "US - Minnesota Permissible Exposure Limits (PELs)", "US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants", "US ACGIH Threshold Limit Values (TLV)", "US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants", "US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory", "US OSHA Permissible Exposure Levels (PELs) - Table Z1"
ethyl butyl acetate(123-66-0) is found on the following regulatory lists	"US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory"
glyceryl triacetate(102-76-1) is found on the following regulatory lists	"US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory"

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	Υ
Korea - KECI	Υ
New Zealand - NZIoC	Υ
Philippines - PICCS	Υ
USA - TSCA	Υ
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

## **SECTION 16 OTHER INFORMATION**

# Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

## www.chemwatch.net

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.