

# **FW-BTE N&A Butter Toffee Flavor**

Flavor West Manufacturing, LLC.

Version No: **2.4**Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Chemwatch Hazard Alert Code: 2

Issue Date: 04/29/2021 Print Date: 04/29/2021 Initial Date: 04/29/2021 L.GHS.USA.EN

### SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

### **Product Identifier**

Product name	FW-BTE N&A Butter Toffee Flavor
Synonyms	Not Available
Other means of identification	Not Available

### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified	Use according to manufacturer's directions
uses	coo docoraing to manaracturor o anotherio

### Details of the manufacturer/importer

Registered company name	Flavor West Manufacturing, LLC.
Address	29400 Hunco Way, Lake Elsinore CA 92530 United States
Telephone	(951) 893-5120
Fax	(714) 276-1621
Website	www.FlavorWest.com
Email	Flavor@FlavorWest.com

# **Emergency telephone number**

Association / Organisation	Chemwatch
Emergency telephone numbers	see below
Other emergency telephone numbers	see below

### **CHEMWATCH EMERGENCY RESPONSE**

Primary Number	Alternative Number 1	Alternative Number 2	
877 715 9305	+612 9186 1132	Not Available	

Once connected and if the message is not in your prefered language then please dial 01

Una vez conectado y si el mensaje no está en su idioma preferido, por favor marque 02

# **SECTION 2 HAZARDS IDENTIFICATION**

### Classification of the substance or mixture

Version No: 2.4 Page 2 of 11 Issue Date: 04/29/2021 Print Date: 04/29/2021

#### **FW-BTE N&A Butter Toffee Flavor**



**GHS Classification** 

Skin Corrosion/Irritation Category 2, Serious Eye Damage Category 1

### Label elements

#### **GHS** label elements





SIGNAL WORD

**DANGER** 

### Hazard statement(s)

H315	Causes skin irritation
H318	Causes serious eye damage

### Precautionary statement(s) Prevention

P280

Wear protective gloves/protective clothing/eye protection/face protection.

### Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor/physician/first aider
P362	Take off contaminated clothing.
P302+P352	IF ON SKIN: Wash with plenty of water and soap
P332+P313	If skin irritation occurs: Get medical advice/attention.

### Precautionary statement(s) Storage

### Precautionary statement(s) Disposal

# **SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**

### **Substances**

See section below for composition of Mixtures

### **Mixtures**

CAS No	%[weight]	Name
57-55-6	70-80	propylene glycol
121-33-5	10-20	vanillin
598-82-3	5-10	lactic acid
118-71-8	1-5	maltol

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

# **SECTION 4 FIRST AID MEASURES**

## Description of first aid measures

**Eye Contact** 

If this product comes in contact with the eyes:

▶ Wash out immediately with fresh running water.

- ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Seek medical attention without delay; if pain persists or recurs seek medical attention.

 Version No: 2.4
 Page 3 of 11
 Issue Date: 04/29/2021

 Print Date: 04/29/2021
 Print Date: 04/29/2021

#### **FW-BTE N&A Butter Toffee Flavor**

	▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.					
Skin Contact	If skin contact occurs:  Immediately remove all contaminated clothing, including footwear.  Flush skin and hair with running water (and soap if available).  Seek medical attention in event of irritation.					
Inhalation	<ul> <li>If fumes or combustion products are inhaled remove from contaminated area.</li> <li>Lay patient down. Keep warm and rested.</li> <li>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>Transport to hospital, or doctor.</li> </ul>					
Ingestion	<ul> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Seek medical advice.</li> </ul>					

### Indication of any immediate medical attention and special treatment needed

- Polyethylene glycols are generally poorly absorbed orally and are mostly unchanged by the kidney.
- Dermal absorption can occur across damaged skin (e.g. through burns) leading to increased osmolality, anion gap metabolic acidosis, elevated calcium, low ionised calcium, CNS depression and renal failure.
- Treatment consists of supportive care.

[Ellenhorn and Barceloux: Medical Toxicology]

Propylene glycol is primarily a CNS depressant in large doses and may cause hypoglycaemia, lactic acidosis and seizures.

- The usual measures are supportive care and decontamination (Ipecac/ lavage/ activated charcoal/ cathartics), within 2 hours of exposure should suffice.
- ▶ Check the anion gap, arterial pH, renal function and glucose levels.

Ellenhorn and Barceloux: Medical Toxicology

# **SECTION 5 FIREFIGHTING MEASURES**

### Extinguishing media

- ▶ Alcohol stable foam.
- Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.

# Special hazards arising from the substrate or mixture

Fire Incompatibility

 Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

### Advice for firefighters

# Fire Fighting

- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- ▶ Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- ▶ Use water delivered as a fine spray to control fire and cool adjacent area.

### Fire/Explosion Hazard

- Combustible.
- Slight fire hazard when exposed to heat or flame.
- ▶ Acids may react with metals to produce hydrogen, a highly flammable and explosive gas.
- ▶ Heating may cause expansion or decomposition leading to violent rupture of containers.

### **SECTION 6 ACCIDENTAL RELEASE MEASURES**

### Personal precautions, protective equipment and emergency procedures

## Minor Spills

- Remove all ignition sources.
- ▶ Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact with the substance, by using protective equipment.

Version No: 2.4 Page 4 of 11 Issue Date: 04/29/2021 Print Date: 04/29/2021

#### **FW-BTE N&A Butter Toffee Flavor**

Chemical Class: alcohols and glycols

For release onto land: recommended sorbents listed in order of priority.

SORBENT TYPE	RANK	APPLICATION	COLLECTION	LIMITATIONS
-----------------	------	-------------	------------	-------------

#### LAND SPILL - SMALL

cross-linked polymer - particulate	1	shovel	shovel	R, W, SS
cross-linked polymer - pillow	1	throw	pitchfork	R, DGC, RT
sorbent clay - particulate	2	shovel	shovel	R,I, P
wood fiber - pillow	3	throw	pitchfork	R, P, DGC, RT
treated wood fiber - pillow	3	throw	pitchfork	DGC, RT
foamed glass - pillow	4	throw	pichfork	R, P, DGC, RT

#### LAND SPILL - MEDIUM

#### **Major Spills**

cross-linked polymer - particulate	1	blower	skiploader	R,W, SS
polypropylene - particulate	2	blower	skiploader	W, SS, DGC
sorbent clay - particulate	2	blower	skiploader	R, I, W, P, DGC
polypropylene - mat	3	throw	skiploader	DGC, RT
expanded mineral - particulate	3	blower	skiploader	R, I, W, P, DGC
polyurethane - mat	4	throw	skiploader	DGC, RT

#### Legend

DGC: Not effective where ground cover is dense

R: Not reusable

I: Not incinerable

P: Effectiveness reduced when rainy

RT:Not effective where terrain is rugged

SS: Not for use within environmentally sensitive sites

W: Effectiveness reduced when windy

Reference: Sorbents for Liquid Hazardous Substance Cleanup and Control;

R.W Melvold et al: Pollution Technology Review No. 150: Noyes Data Corporation 1988

Moderate hazard.

- ▶ Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

### **SECTION 7 HANDLING AND STORAGE**

# Precautions for safe handling

#### Safe handling

- ▶ DO NOT allow clothing wet with material to stay in contact with skin
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

### Other information

- ▶ Material is hygroscopic, i.e. absorbs moisture from the air. Keep containers well sealed in storage.
- Store in original containers.
- ▶ Keep containers securely sealed.

# Conditions for safe storage, including any incompatibilities

### Suitable container

- ▶ Lined metal can, lined metal pail/ can.
- ▶ Plastic pail.
- ▶ Polyliner drum.
- ▶ Packing as recommended by manufacturer.

# Storage incompatibility

▶ Glycols and their ethers undergo violent decomposition in contact with 70% perchloric acid. This seems likely to involve formation of the glycol perchlorate esters (after scission of ethers) which are explosive, those of ethylene glycol and 3-chloro-1,2-propanediol being more powerful than glyceryl nitrate, and the former so sensitive that it explodes on addition of water.

#### Alcohols

- are incompatible with strong acids, acid chlorides, acid anhydrides, oxidising and reducing agents.
- reacts, possibly violently, with alkaline metals and alkaline earth metals to produce hydrogen
- react with strong acids, strong caustics, aliphatic amines, isocyanates, acetaldehyde, benzoyl peroxide, chromic acid,

 Version No: 2.4
 Page 5 of 11
 Issue Date: 04/29/2021

 Print Date: 04/29/2021
 Print Date: 04/29/2021

#### **FW-BTE N&A Butter Toffee Flavor**

- chromium oxide, dialkylzincs, dichlorine oxide, ethylene oxide, hypochlorous acid, isopropyl chlorocarbonate, lithium tetrahydroaluminate, nitrogen dioxide, pentafluoroguanidine, phosphorus halides, phosphorus pentasulfide, tangerine oil, triethylaluminium, triisobutylaluminium
- ▶ should not be heated above 49 deg.

#### PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

### SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Overalls.P.V.C. apron.

▶ Barrier cream.

Other protection

#### Control parameters

### OCCUPATIONAL EXPOSURE LIMITS (OEL)

### **INGREDIENT DATA**

Not Available

### **EMERGENCY LIMITS**

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
propylene glycol	Propylene glycol; (1,2-Propanediol)	30 mg/m3	1300 mg/m3	7900 mg/m3
vanillin	Vanilin	10 mg/m3	10 mg/m3	310 mg/m3
lactic acid	Lactic acid	0.47 mg/m3	5.2 mg/m3	700 mg/m3

Ingredient	Original IDLH	Revised IDLH
propylene glycol	Not Available	Not Available
vanillin	Not Available	Not Available
lactic acid	Not Available	Not Available
maltol	Not Available	Not Available

### MATERIAL DATA

for propylene glycol:

Saturated vapour concentration @ 20 deg C.= 65.8 ppm, 204.6 mg/m3; i.e higher concentrations can only occur as aerosols or at higher temperatures. Odour Threshold: Practically odourless.

A small number of individuals show skin irritation or sensitisation from repeated or prolonged exposure to propylene glycol. A workplace environmental exposure limit (WEEL) has been established by AIHA and is thought to be protective against systemic effects.

### **Exposure controls**

### Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. **Appropriate** The basic types of engineering controls are: engineering controls Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Personal protection Safety glasses with side shields. Chemical goggles. Eye and face ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy protection document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. Skin protection See Hand protection below ▶ Wear chemical protective gloves, e.g. PVC. ▶ Wear safety footwear or safety gumboots, e.g. Rubber NOTE: Hands/feet protection ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. ▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. **Body protection** See Other protection below

 Version No: 2.4
 Page 6 of 11
 Issue Date: 04/29/2021

 Print Date: 04/29/2021
 Print Date: 04/29/2021

#### **FW-BTE N&A Butter Toffee Flavor**

Thermal hazards

Not Available

### Recommended material(s)

#### GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

#### "Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

FW-BTE N&A Butter Toffee Flavor

Material	СРІ
BUTYL	С
NATURAL RUBBER	С
NATURAL+NEOPRENE	С
NEOPRENE	С
NEOPRENE/NATURAL	С
NITRILE	С
PE/EVAL/PE	С
PVA	С
PVC	С
VITON	С

<sup>\*</sup> CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE**: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

#### Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

#### ^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

## **SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

### Information on basic physical and chemical properties

Appearance	Clear to light amber		
Physical state	Liquid	Relative density (Water = 1)	1.08
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	>93.00	Taste	Butter toffee
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available

Version No: 2.4 Page **7** of **11** Issue Date: 04/29/2021 Print Date: 04/29/2021

**FW-BTE N&A Butter Toffee Flavor** 

Vapour density (Air = Not Available VOC g/L Not Available

# **SECTION 10 STABILITY AND REACTIVITY**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

# **SECTION 11 TOXICOLOGICAL INFORMATION**

	The material is not thought to produce respirator	riritation (as classified by EC Directives using animal models).			
	Nevertheless inhalation of vapours, fumes or ae	rosols, especially for prolonged periods, may produce respiratory discomfor			
Inhaled	and occasionally, distress.				
	Inhalation of vapours may cause drowsiness and of reflexes, lack of coordination and vertigo.	dizziness. This may be accompanied by narcosis, reduced alertness, loss			
	Accidental ingestion of the material may be dame				
		e central nervous system depression in humans following ingestion of 60 m			
Ingestion Symptoms included increased heart-rate (tachycardia), excessive sweating (diaphoresis) and grand mal seizu month child who ingested large doses (7.5 ml/day for 8 days) as an ingredient of vitamin preparation.					
	· · · · · · · · · · · · · · · · · · ·	lycaemia (low levels of glucose in the blood stream) among susceptible			
		cause hypogrycaemia (low levels of glucose in the blood stream) among susceptible llar weakness, incoordination and mental confusion.			
	•	vidence exists, or practical experience predicts, that the material either			
	· ·	in a substantial number of individuals following direct contact, and/or tion when applied to the healthy intact skin of animals (for up to four hours			
		hours or more after the end of the exposure period.			
Skin Contact		ed or repeated exposure; this may result in a form of contact dermatitis			
		(nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to			
	blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.				
		<u>'</u>			
	Irritation of the eyes may produce a heavy secretion of tears (lachrymation).  Limited evidence or practical experience suggests, that the material may cause eye irritation in a substantial number of individuals. Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.				
Eye					
·					
		term occupational exposure may produce cumulative health effects			
	involving organs or biochemical systems.	n contact with the material is capable either of inducing a sensitisation			
Chronic	·	d/or of producing positive response in experimental animals.			
	<u>-</u>	sitising principal following the regular use of topical creams by eczema			
	patients. A study of 866 persons using a formulation containing propylene glycol in a patch test indicated that propylene				
	glycol caused primary irritation in 16% of expose	d individuals probably caused by dehydration.			
	TOXICITY	IRRITATION			
FW-BTE N&A	TOMOTT	IMMANON			
Butter Toffee Flavorr	Not Available	Not Available			

Butter Tollee Flavori	Not Available	Not Available
	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg <sup>[1]</sup>	Eye (rabbit): 100 mg - mild
propylene glycol	Oral (rat) LD50: 20000 mg/kgd <sup>[2]</sup>	Eye (rabbit): 500 mg/24h - mild
		Skin(human):104 mg/3d Intermit Mod
		Skin(human):500 mg/7days mild

Version No: 2.4 Page 8 of 11 Issue Date: 04/29/2021 Print Date: 04/29/2021

### **FW-BTE N&A Butter Toffee Flavor**

	TOXICITY			IRRITATION	
vanillin	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>			Not Available	
	Oral (rat) LD50: 1400 mg/kg <sup>[1]</sup>				
	. ,				
	TOXICITY	IRRITA	ATION		
lactic acid	M			0 mg SEVERE	
lactic acid	Oral (rat) LD50: 3543 mg/kg <sup>[1]</sup>			-	
	Orai (rat) LD50: 3543 mg/kg <sup>c-1</sup>	Skin (	(rappit): 5 mg	g/24h SEVERE	
maltol	TOXICITY	IRRITATION			
	Oral (rat) LD50: 1410 mg/kge <sup>[2]</sup>	Skin (rabbit):	500 mg/24h	moderate	
Legend:	Value obtained from Europe ECHA Registered Substance	es - Acute toxici	ity 2.* Value	obtained from manufacturer's msds.	
_	Unless otherwise specified data extracted from RTECS -	Register of Toxic	Effect of ch	emical Substances	
	No significant acute toxicological data identified in litera	ure search.			
FW-BTE N&A	The acute oral toxicity of propylene glycol is very low, a	• .	•		
Butter Toffee Flavor	damage in humans. Serious toxicity generally occurs or high intake over a relatively short period of time. It wou				
	or supplements, which contain at most 1 g/kg of PG.			, ,	
	The material may cause skin irritation after prolonged or (nonallergic). This form of dermatitis is often characteris			•	
PROPYLENE GLYCOL	Histologically there may be intercellular oedema of the	•	, ,	, .	
PROFILENE GLICOL	epidermis.				
	The acute oral toxicity of propylene glycol is very low, and large quantities are required to cause perceptible health damage in humans.				
	-				
	For certain benzyl derivatives:				
All members of this group (benzyl, benzoate and 2-hydroxybenzoate (salicylate) ester directly to an oxygenated functional group (aldehyde or ester) that is hydrolysed and			-		
VANILLIN	derivative. As a stable animal metabolite, benzoic acid derivatives are efficiently excreted primarily in the urine. These				
	I in both aquatic and terrestrial species. The similarity of their toxicologic properties se common metabolic pathways.				
	Miosis, somnolence, muscle weakness, coma, respiratory stimulation, maternal effects involving ovaries, fallopian tubes				
	uterus, cervix and vagina recorded.				
	for acid mists, aerosols, vapours				
	Data from assays for genotoxic activity in vitro suggest	-			
	the pH falls to about 6.5. Cells from the respiratory tract have not been examined in this respect. Mucous secretion may				
LACTIC ACID	protect the cells of the airways from direct exposure to inhaled acidic mists, just as mucous plays an important role in protecting the gastric epithelium from its auto-secreted hydrochloric acid. In considering whether pH itself induces				
	genotoxic events in vivo in the respiratory system, comparison should be made with the human stomach, in which gastric				
	juice may be at pH 1-2 under fasting or nocturnal condit can range from <5 to > 7 and normally averages 6.2.	ons, and with th	ie human uri	nary bladder, in which the pH of urine	
	5,,				
	Asthma-like symptoms may continue for months or eve to a non-allergenic condition known as reactive airways		-		
	exposure to high levels of highly irritating compound. Ki	-			
	preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within				
MALTOL	minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic				
1111 121 02	inflammation, without eosinophilia, have also been inclu		-		
	Oral (rat) TDLo: 90000 mg/kg/90d-I Eye : Mild Maltol at	-	=		
	maximisation test. * There were no compound-related effects in a three generation reproduction in the rat.* FAO/ we evaluated that the level causing no toxicological effect is 100 mg/kg bw in rat* FAO/WHO estimated in 1974 that				
	acceptable daily intake (ADI) for man is 1mg/kg bw. 7) The Council of Europe (1974) listed Maltol, giving an ADI of 1				
	mg/kg 6)* Beijing TianLiHai Chemical Company Co. Ltd	MSDS			
	0	0			
Acute Toxicity	0	Carcinogenicit	ty 🛇		
Skin Irritation/Corrosion	<b>~</b>	Reproductivit	ty 🛇		

 Version No: 2.4
 Page 9 of 11
 Issue Date: 04/29/2021

 Print Date: 04/29/2021
 Print Date: 04/29/2021

#### **FW-BTE N&A Butter Toffee Flavor**

Serious Eye Damage/Irritation	•	STOT - Single Exposure	0
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0
Mutagenicity	0	Aspiration Hazard	0

Legend:

✓ – Data required to make classification available

🗶 – Data available but does not fill the criteria for classification

Data Not Available to make classification

### **CMR STATUS**

Not Applicable

#### **SECTION 12 ECOLOGICAL INFORMATION**

### **Toxicity**

#### NOT AVAILABLE

Ingredient	Endpoint	Test Duration	Effect	Value	Species	BCF
propylene glycol	Not Available					
vanillin	Not Available					
lactic acid	Not Available					
maltol	Not Available					

for simple alpha-hydroxy carboxylic acids and their salts:

Available experimental and estimated data for simple alpha-hydroxy carboxylic acids indicate that the members of this cluster have a low acute and chronic aquatic toxicity

Propylene glycol is known to exert high levels of biochemical oxygen demand (BOD) during degradation in surface waters. This process can adversely affect aquatic life by consuming oxygen needed by aquatic organisms for survival. Large quantities of dissolved oxygen (DO) in the water column are consumed when microbial populations decompose propylene glycol.

Sufficient dissolved oxygen levels in surface waters are critical for the survival of fish, macro-invertebrates, and other aquatic organisms.

### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
propylene glycol	LOW	LOW
vanillin	LOW	LOW
lactic acid	LOW	LOW
maltol	LOW	LOW

# **Bioaccumulative potential**

Ingredient	Bioaccumulation
propylene glycol	LOW (BCF = 1)
vanillin	LOW (LogKOW = 1.21)
lactic acid	LOW (LogKOW = -0.72)
maltol	LOW (LogKOW = 0.09)

### Mobility in soil

Ingredient	Mobility
propylene glycol	HIGH (KOC = 1)
vanillin	LOW (KOC = 38.45)
lactic acid	HIGH (KOC = 1)
maltol	HIGH (KOC = 1)

### **SECTION 13 DISPOSAL CONSIDERATIONS**

# Waste treatment methods

Product / Packaging disposal

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

Version No: 2.4 Page 10 of 11 Issue Date: 04/29/2021 Print Date: 04/29/2021

#### **FW-BTE N&A Butter Toffee Flavor**

A Hierarchy of Controls seems to be common - the user should investigate:

- ▶ Reduction
- Reuse
- Recycling
- ▶ Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.

### **SECTION 14 TRANSPORT INFORMATION**

### **Labels Required**

**Marine Pollutant** 

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

### Transport in bulk according to Annex II of MARPOL 73 / 78 and the IBC code

Source	Ingredient	Pollution Category
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	lactic acid	Z

# **SECTION 15 REGULATORY INFORMATION**

### Safety, health and environmental regulations / legislation specific for the substance or mixture

propylene glycol(57-55-6) is found on the following regulatory lists	"US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)","US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values","US AIHA Workplace Environmental Exposure Levels (WEELs)","US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants","US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory"
vanillin(121-33-5) is found on the following regulatory lists	"US AIHA Workplace Environmental Exposure Levels (WEELs)","US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory"
lactic acid(598-82-3) is found on the following regulatory lists	"US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory"
maltol(118-71-8) is found on the following regulatory lists	"US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory"

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	Y
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

Version No: 2.4 Page 11 of 11 Issue Date: 04/29/2021 Print Date: 04/29/2021

#### **FW-BTE N&A Butter Toffee Flavor**

**SECTION 16 OTHER INFORMATION** 

### Other information

# Ingredients with multiple cas numbers

Name	CAS No
lactic acid	10326-41-7, 50-21-5, 598-82-3, 79-33-4

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

#### www.chemwatch.net

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.